



Care & Maintenance

TEK-CRETE Urethane Concrete Chemical Resistant Flooring

Congratulations on choosing the finest quality chemical resistant flooring available. Your new Dex-O-Tex Tek-Crete chemical resistant seamless floor covering system will provide years of trouble free service with a minimum of maintenance. Just follow the recommendations below to maximize the performance and life of your floor covering.

Cleaning

Cleaning your new Dex-O-Tex floor is simple. Just wash with a mild solution such as "Simple Green" or "Ivory Liquid". Use a bristle brush to remove tough stubborn stains or residual compounds. Rinse thoroughly with clean water.

Regular cleaning will prevent build-up of residue which can make the floor surface slippery when wet.

Maintenance

The Dex-O-Tex Tek-Crete Chemical resistant flooring incorporates a hybrid of high tech cements and polyurethane resin technology which provides a high heat resistant and chemical resistant flooring system. Tek Crete does not require any on going periodic maintenance. Only areas that have been damaged from physical abuse need to be maintained by localized replacement.

The system is designated to withstand normal everyday wear and tear, direct exposure to thermal and chemical elements. Harsh chemicals should be cleaned from the surface as soon as possible. Over an extended period of time the traffic topping needs to be resurfaced with Dex-O-Tex Tek-Crete SL. This is required when traffic patterns become visible in the flooring. This will be approximately 7 to 10years in normal traffic areas and every 5 to 8 years in high traffic areas such as stairways and access corridors.

If your Dex-O-Tex flooring system becomes loose or de-bonded from the substrate for any reason, call us or the installing contractor immediately. Any problem with the flooring should be addressed immediately to prevent further damage.

Common Problems to Avoid

Do not expose floor to constant temperatures in excess of 300°.

Do not allow water migration through any protrusions in the flooring system

Avoid standing water by properly designing slope before application of the flooring system

Avoid heavy rolling loads with steel wheels

Floor areas subject to scratching by tracking of sand or grit from outside areas should be swept frequently



DEX-O-TEX PRODUCT LINE Crossfield Products Corp.

West Coast Office 3000 E. Harcourt Street Rancho Dominguez, CA 90221 310-886-9100 310-886-9119 fax	East Coast Office 140 Valley Road Roselle Park, NJ 07204 908-245-2800 908-245-0659 fax
---	---

www.dexotex.com